Double Action Tact





TSFA type

TSFA02 Series



(size : $5.7 \times 3.5 \times 3.75$) Double Action Type Tact Swith

■ Features

Sharp click feel with a positive tactile feedback. Ultraminiature and light weight structure suitbable for high density mounting, Economical but reliable. Insert molding in the contact with special treatment prevents flux build-up during soldering and permits auto-dipping

Applications

Cameras, digital still

cameras

Digital video camcorders

Compact portable devices

Dimensions

TSFA02-DTAA

	Main	Specifications	
Rat	ing		

Rating	50mA 12V DC		
Travel	1st 0.4±0.1mm 2st 0.6±0.1mm		
Contact Resistance	100mΩ Max		
Operating temperature	-20°C~70°C (45%~85% RH)		
Operating Force	1st 100±30gf 2st 250±60gf		
Operating Life(Cycle)	100, 000		

■ Products Line

TSFA02 - DJAA

Products No.	0/D	Terminal Type	Guide Boss	Drawing No
DJAA	Horizontal	J-bent	With-out	1

No.	3D Style	Dimension Type (Unit : mm)	PCB pattern dimension Circuit Diagram
1	DJAA	5.7	P.C.B. 1.6 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2