# Double Action Tact





# TSFA type

# TSFA03 Series









Double Action Type Tact Swith

#### Features

Sharp click feel with a positive tactile feedback. Ultraminiature and light weight structure suitbable for high density mounting, Economical but reliable. Insert molding in the contact with special treatment prevents flux build-up during soldering and permits auto-dipping

### Applications

Cameras, digital still cameras

Digital video camcorders

Compact portable devices

## ■ Main Specifications

(size :  $6.4 \times 6.4 \times 1.5$ )

Rating	50mA 12V DC		
Travel	1st 0.5±0.1mm 2st 0.7±0.1mm		
Contact Resistance	100mΩ Max		
Operating temperature	-20°C~70°C (45%~85% RH)		
Operating Force	1st 100±30gf 2st 260±60gf		
Operating Life(Cycle)	30, 000		

### ■ Products Line

TSFA03 - C□□A

(Terminal Type) (Height)

Products No.	0/D	Terminal Type	Guide Boss	Drawing No
CFAA	Vertical			1
CFBA		F-bent		2
CFCA			W: 41	
СЈАА			With	3
СЈВА		J-bent		4
CJCA				4

Terminal Type□		
CF	F	
СЈ	J	

Height □		
3.0mm	В	
3.8mm	С	

No.	3D Style	Dimension Type (Unit : mm)	PCB pattern dimension Circuit Diagram
1	CFAA	500 FE 1 100	8.5 5.4 1.5 0.00 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
2	CFBA/CFCA	0.5 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0	OFF S S S S D DUMMY  1st ACTION S S S S D DUMMY  ACTION S S S S D DUMMY  ACTION S S S D DUMMY
3	CJAA	6.4	7.4 5.4 5.4 1.5 0.000 0.00
4	CJBA/CA	6.4 6.4 6.4 6.4 6.4 6.8 Max. 6.8 Max. 6.8 Max. 6.8 Max. 6.8 Max. 6.8 Max. 6.8 Max. 6.8 Max. 6.8 Max. 6.8 Max. 6.3 Max. 6.3 Max. 6.4 Max. 6.5 Max. 6.5 Max. 6.6 Max. 6.7 Max. 6.7 Max. 6.8 Max. 6	OFF

