Double Action Tact





TSFA type

TSFA04 Series



(size : $6.2 \times 6.6 \times 2.0$)

Double Action Type Tact Swith

■ Features

These surface-mounting type keyboard switches are ideal for high density mounting. A single-pole-double-throw type offers a double action, turning on the first contact with the first push and the second step by pushing agin. Reflow solderable.

Applications

Operating switches in all types of electronic equipment such as audio apparatus office equipment, communications apparatus, measuring instruments, TV sets, VCRs, etc

■ Main Specifications

Rating	50mA 12V DC		
Travel	1st 0.4±0.1mm 2st 0.6±0.1mm		
Contact Resistance	100mΩ Max		
Operating temperature	-20°C~70°C (45%~85% RH)		
Operating Force	1st 100±50gf 2st 400±50gf		
Operating Life(Cycle)	20, 000		

■ Products Line

TSFA04 - CSAA

Products No.	O/D	Terminal Type	Guide Boss	Drawing No
CSAA	Vertical	S-bent	With	1

Dimensions

TSFA04-CSAA

No.	3D Style	Dimension Type (Unit : mm)	PCB pattern dimension Circuit Diagram
1	CSAA	8 6.2 9 9 9 3	2-\phi 1.3\pm 0.05hold 8.4 4 4-1.4x1.6land OFF 1st ON 2nd ON