5 Direction Tact switch



TSFB type

TSFB09 Series

Features

Available shprp click feel with a positive tactile feedback.

Ultraminiature and light weight structure suitable for high density mounting. Economic but high reliability.

Applications

Operation switches for menu scrolling and confirmation for portable equipment Compact, portable unit such as cameras, PDA etc.



(size : $10.3 \times 10.3 \times 1.5$) 5 Direction Tact switch

Main Specifications

| Rating | 20mA 12V DC | |
|-----------------------|------------------------------|--|
| Travel | 4 Direction 0.25 \pm 0.1mm | |
| | Center push 0.25±0.1mm | |
| Contact Resistance | 100mΩ Max | |
| Operating temperature | -20°C~70°C (45%~85% RH) | |
| Operating Force | 4 Direction 160±80gf | |
| | Center push 320 ± 150 gf | |
| Operating Life(Cycle) | 200, 000 | |

Products Line

TSFB09 - MFAA

| Products No. | 0/D | Terminal Type | Guide Boss | Drawing Nc |
|--------------|----------|---------------|------------|------------|
| MFAA | Vertical | F-bent | Without | 1 |

T S F

Dimensions

TSFB09-MFAA

| No. | 3D Style | Dimension Type (Unit : mm) | PCB pattern dimension Circuit Diagram |
|-----|----------|----------------------------|---|
| 1 | MFAA | Operating direction | |

