5 Direction Tact switch





TSFB type

TSFB11 Series



 $(size : 9.8 \times 9.8 \times 5.05)$

5 Direction Tact switch

Features

Available shprp click feel with a positive tactile feedback.

Insert molding in the contact with special treatment prevents flux build-up during soldering and permits auto-dipping.

Applications

Operation switches for menu scrolling and confirmation for portable equipment Compact, portable unit such as cameras, PDA etc.

■ Main Specifications

Rating	20mA 12V DC	
Travel	4 Direction 0.25 ± 0.1 mm	
	Center push 0.25±0.1mm	
Contact Resistance	100mΩ Max	
Operating temperature	-20°C~70°C (45%~85% RH)	
Operating Force	4 Direction 160±80gf	
	Center push $320\pm150\mathrm{gf}$	
Operating Life(Cycle)	200, 000	

■ Products Line

TSFB11 - MJAA

Products No.	0/D	Terminal Type	Guide Boss	Drawing No
МЈАА	Vertical	J-bent	With	1

Dimensions

TSFB11-MJAA

No.	3D Style	Dimension Type (Unit : mm)	PCB pattern dimension Circuit Diagram
1	МЈАА	D Compt of the Com	
		2-63.6	Com4 E Com3 D Com1 Com5 Com2