#### SWITCHES

# 5 Direction Tact switch



## TSFB type

### TSFB12 Series

#### Features

A sharp click feel with tactile feedback characteristic. The stem has a joint shape which allows a knob to be attached on. SMD type allowing reflow soldering.

#### Applications

Cursor operations for devices requiring graphic input. Adjustments of TVS,video

recorders, etc.

Adjustment of audio devices such as equalizers.



(size :  $10.0 \times 10.0 \times h$ )

5 Direction Tact switch

#### Main Specifications

<u> </u>				
Rating	50mA 12V DC			
Travel	4 Direction $0.25\pm0.1$ mm			
	Center push 0.15±0.1mm			
Contact Resistance	500mΩ Max			
Operating temperature	-20°C~70°C (45%~85% RH)			
Operating Force	4 Direction 130±50gf			
	Center push $250\pm50{ m gf}$			
Operating Life(Cycle)	200, 000			

#### Products Line

TSFB12 -  $M\Box\Box A$ 

(Bent) (Height)

Products No.	0/D	Terminal Type	Guide Boss	Drawing No
MAAA	Vertical	StAndard	With-out	1
MJAA		J-bent	With-out	2
MABA		StAndard	With-out	3
MJCA		J-bent	With-out	4

Bent 🗆		
StAndard	А	
J-bent	J	

Height 🗆			
7.1mm	А		
10. Omm	В		
8.6mm	С		





### TSFB12−M□□A

MAAA 1		A O O O O Center
	0 g	B @-o ¥ o-⑤ D C ③ O Common
MJAA 2		
		A O Center B O C O Common
3 MABA		4-41.2 Volum 
	315 215	A O Center B O D C O Common
4 MJCA		
		A O Center B O O D C O O Common

170

T S F