SLIDE switch





TSSA type

TSSA13 Series







(size : $12.5 \times 3.0 \times 2.0$) Sn

Snap-in & Surface mount Type

■ Features

Snap-in & Surface mount type slide switch. Outline dimension 12.5mm X 3.0mm Double or single side Recoil operating type.

■ Applications

For keylocking mobile phones, MP3
For selecting modes of digital camcorders, digital cameras.
Operating signal input switches, etc.

■ Main Specifications

Rating	DC 24V 25mA
Travel	2.0 ± 0.3 mm
Contact Resistance	10mΩ Max
Operating temperature	-20°C~70°C (45%~85% RH)
Operating Force	250±100gf
Operating Life(Cycle)	10,000

■ Products Line

TSSA13 - | | | | | | | |

(Products No.)

Products No.	Operating Type	Soldering Type	Guide Boss	Drawing No
BP00AT	Double-side recoil		Without	1
DFOWAT	Double-side recoil		With	2
DFOWAR	Single-side recoil to Right	SMT	With	3
DFOWAL	Single-side recoil to Left		With	4

No.	3 - 🗆 🗆 🗆 🗆 🗎 3D Style	Dimension Type (Unit : mm)	PCB pattern dimension Circuit Diagram
1	BPOOAT	4.0 0.5 8.0 2.0TRAVEL 1.0 1.5	4-#0.6 Holes 4-#0.6 Holes 4.0 8.0
		2.0 2.0 2.0 2.0 2.0 2.0 2.0 2.0 2.0 2.0	(A) (B) (C) (D) (D) (D) (D) (D) (D) (D) (D) (D) (D
2	DFOWAT	2.0 TRAVEL 2.0 TRAVEL 2.0 0.65	90.8 Holes 10.2
		4.0 0.5 8.0 12.3 12.5	(A) (B) (C) (D) (D) (D) (D) (D) (D) (D) (D) (D) (D
3	DFOWAR	2.0(TRAVEL) A B C	2 -Ø0.8 HOLES 10.25 4-1-1-1-8
		2-0.7	
4	DFOWAL	2.0(TRAVEL) 2.0(TRAVEL)	2 -Ø0.8 HOLES 10.25 4 -1 4 -8
		2.0(IRAVEL) 2.0(IRAVEL) 9 9 2.0 9 2.	