TACT switch





TSTB type

TSTB17 Series



(size: $4.8 \times 4.8 \times 0.55$) Vertical push Surface mount type

Features

Surface mount type tact switch. Reflow solderable.

Vertical operating direction.

Dust&Moisture protective structure.

Applications

Various controls for devices in automotive.

Controls for image/sound devices, radio equipment.

Operating signal input switches,

etc.

■ Main Specifications

Rating	50mA 12V DC	
Travel	0.2±0.1mm	
Contact Resistance	100mΩ Max	
Operating temperature	-20°C~70°C (45%~85% RH)	
Bounce	10m sec Max	
Operating Force	160±40gf 250±60gf	
Operating Life(Cycle)	100,000 50,000	

Products Line

TSTB17 (Products No.) (O/F)

Products No.	O/F	O/D	Terminal Type	Guide Boss	Drawing No
CJOOA		Vertical	J-bent	With-out	1

Operating Force	160±40gf	16	250±60gf	25
-----------------	----------	----	----------	----

Dimensions

13101	./		
No.	3D Style	Dimension Type (Unit : mm)	PCB pattern dimension Circuit Diagram
1	CJOOA □□	4.8 1.7 (a) (b) (c) (c) (c) (c) (c) (c) (c) (c	1.8. 4.0