

TACT switch



TSTB type

TSTB18 Series



(size : 4.1×4.1×0.58)

Vertical push Surface mount type

T
S
T

■ Features

- Surface mount type tact switch.
- Reflow solderable.
- Vertical operating direction.
- Dust&Moisture protective structure.

■ Applications

- Various controls for devices in automotive.
- Controls for image/sound devices, radio equipment.
- Operating signal input switches, etc.

■ Dimensions

TSTB18-□□□□□ □□

■ Main Specifications

Rating	20mA 15V DC		
Travel	0.2±0.1mm		
Contact Resistance	100mΩ Max		
Operating temperature	-20°C~70°C (45%~85% RH)		
Bounce	10m sec Max		
Operating Force	160±40gf	250±60gf	350±80gf
Operating Life(Cycle)	200,000	100,000	50,000

■ Products Line

TSTB18 - □□□□□ □□
(Products No.) (O/F)

Products No.	O/F	O/D	Terminal Type	Guide Boss	Drawing No
CJOOA	□□	Vertical	J-bent	With-out	1

Operating Force □□	160±40gf	16	250±60gf	25	350±80gf	35
--------------------	----------	-----------	----------	-----------	----------	-----------

No.	3D Style	Dimension Type (Unit : mm)	PCB pattern dimension Circuit Diagram
1	CJOOA □□		