

TACT switch



TSTD type

TSTD02 Series



(size : 6.2×6.2×h) Vertical push Surface mount type

T
S
T

■ Features

- Surface mount type tact switch.
- Reflow solderable.
- Vertical operating direction.
- Dust&Moisture protective structure.

■ Applications

- Various controls for devices in automotive.
- Controls for image/sound devices, radio equipment.
- Operating signal input switches, etc.

■ Dimensions

TSTD02-□□□□□ □□

■ Main Specifications

Rating	50mA 12V DC		
Travel	0.25±0.1mm		
Contact Resistance	100mΩ Max		
Operating temperature	-20°C~70°C (45%~85% RH)		
Bounce	5m sec Max		
Operating Force	160±40gf	250±60gf	350±100gf
Operating Life(Cycle)	100,000	100,000	50,000

■ Products Line

TSTD02 - □□□□□ □□
(Products No.) (O/F)

Products No.	O/F	O/D	Terminal Type	Guide Boss	Drawing No
CS00□	□□	Vertical	S-bent	With-out	1

Height □	
2.5mm	A
3.1mm	B
3.4mm	C

Operating Force □□	
160±40gf	16
250±60gf	25
350±100gf	35

No.	3D Style	Dimension Type (Unit : mm)	PCB pattern dimension Circuit Diagram
1	CS00□ □□		