# TACT switch





## TSTE type

### TSTE02 Series





(size :  $7.8 \times 7.8 \times 5.0$ ) Long travel tact switch

#### **■** Features

Supplied with radial taping.

Allows automatic insertion onto printed circuit board with the radial auto insertion machine.

#### ■ Applications

Operating switches in all types of electronic equipment such as audio devices, office devices, communication devices, measuring instruments, TVs, video recorders, automotive sets, etc.

#### ■ Main Specifications

Rating	50mA 12V DC		
Travel	1.2±0.1mm		
Contact Resistance	100mΩ Max		
Operating temperature	-20°C~70°C (45%~85% RH)		
Bounce	5m sec Max		
Operating Force	130±30gf 250±60gf		
Operating Life(Cycle)	100, 000 100, 000		

#### ■ Products Line

Products No.	0/F	0/D	Terminal Type	Guide Boss	Drawing No
AAOOA		Vertical	StAndard	With-out	1
APOOA		verticai	P-bent	With-out	2

Operating For	се 🗆 🗆
130±30gf	13
250±60gf	25

TSTE02-

No.	3D Style	Dimension Type (Unit : mm)	PCB pattern dimension Circuit Diagram
1	AAOOA 🗆 🗆		4-Ø1 Holes
2	APOOA □□	8.2 8.2 95.9 95.9 95.9 10.3	3 4 2-ø1.0 hole 5.0 1-002