# TACT switch



## TSTF type

### TSTF05 Series

# T S T

#### Features

Snip-in type, which can be directly mounted onto a PC board. Part or output terminals can be used as jumper leads, thus making circuit design easy.

#### Applications

For operationg various electronic devices such as washing machines requiring water proof construction



#### (size:7. $4 \times 7.4 \times 5.0$ ) Waterproof Type

#### Main Specifications

Rating	50mA 12V DC		
Travel	PLASTIC:0.25±0.15mm RUBBER:0.45±0.2mm		
Contact Resistance	100mΩ Max		
Operating temperature	-20°C~70°C (45%~85% RH)		
Bounce	5m sec Max		
Operating Force	160±40gf 250±60gf		
Operating Life(Cycle)	100,000 50,000		

#### Products Line

(Products No.) (O/F)

(Knob)

Products No.	0/F	0/D	Terminal Type	Guide Boss	Drawing No
AAOOA		Vertical	StAndard	With-out	1
BPOOA		Horizontal	P-bent	With-out	2
CSOOA		Vertical	S-bent	With-out	3

Operating For	ce 🔲
$160 \pm 40 \mathrm{gf}$	16
$250\pm60{ m gf}$	25

	KNOB & TRAVEL(mm) 🔲		
	PLASTIC: $0.25\pm0.15$ n	А	
	RUBBER: 0. $45 \pm 0.2$ mm	В	



Dimensions

### TSTF05-00000000

No.	3D Style	Dimension Type (Unit : mm)	PCB pattern dimension Circuit Diagram	
1				
2	BP00A 🗆 🗆 – 🗆		(1-0° 0-2	
3	CSOOA 🗆 🗆 – 🗆			

