

# TACT switch

## TSTL type

## TSTL02 Series



(size : 8.2×7.6×h)

Vertical push Surface mount type

T  
S  
T

### ■ Features

Surface mount type tact switch.  
 Reflow solderable.  
 Vertical operating direction.  
 Dust&Moisture protective structure.

### ■ Applications

Various controls for devices in automotive.  
 Controls for image/sound devices, radio equipment.  
 Operating signal input switches, etc.

### ■ Dimensions

TSTL02-□□□□□ □□

### ■ Main Specifications

Rating	50mA 12V DC	
Travel	0.25±0.1mm	
Contact Resistance	100mΩ Max	
Operating temperature	-20°C~70°C (45%~85% RH)	
Bounce	5m sec Max	
Operating Force	180±50gf	250±60gf
Operating Life(Cycle)	100,000	50,000

### ■ Products Line

TSTL02 - □□□□□ □□  
 (Products No.) (O/F)

Products No.	O/F	O/D	Terminal Type	Guide Boss	Drawing No
AA00□	□□	Vertical	StAndard	With-out	1

Height □			
13.0mm	A	14.5mm	D
13.5mm	B	26.0mm	E
14.0mm	C		

Operating Force □□	
180±50gf	18
250±60gf	25

No.	3D Style	Dimension Type (Unit : mm)	PCB pattern dimension Circuit Diagram
1	AA00□ □□		